




POWER PACK

COOLING DISTANCE 125'

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise



MMPP4301



5-15P



ETL Listed.

www.micromatic.com • 1 (866) 327-4159

1/3 HP COMPRESSOR

Job Number: _____ Location: _____

Part No.	Description	Shipping Weight	Box Dimensions
□ MMPP4301	Air Cooled	55 kg	787mm L x 533mm W x 813mm H
		120 lbs	31"L x 21"W x 32"H
□ MMPP4301-WC	Water Cooled	55 kg	787mm L x 533mm W x 813mm H
		120 lbs	31"L x 21"W x 32"H

Operating Performance

Compressor	1/3 HP	Water Cooled Model	
BTU per hour	2,300	Water Inlet & Outlet Fitting	Female 3/8" NPT
Plug Type (NEMA #)	5-15P	Minimum Water Pipe Size	3/8"
Voltage	115	Inlet Water Pressure	Less than 80 PSIG
Running	12.9A	Water Usage	.3 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
Refrigerant	R-134a	Condenser Inlet Water Temperature	75°F
Charge	0.34 kg (12 oz)	Maximum Outlet Water Temperature	95°F to minimize water scaling with the condenser.
Bath Capacity	43.5 litre (11.5 Gallons)		
Pump Type	Vane		
Inlet Barb	9.52mm (3/8")		
Outlet Barb	9.52mm (3/8")		

Dimensions

