



PMP535 EURO30 WINE PUMP

QUICK START GUIDE

1. Have a professional electrician wire your pump with the appropriate plug. If this is your first use, we recommend spraying a food grade lubricant (Silicone Spray) inside the pump head as the impeller can set in transit.
2. This PMP535 is a self-priming pump, meaning it will pump air, enabling it to draw fluid from your source. The impeller must never run dry or it will wear out very quickly. Prior to connecting lines before each use we recommend pouring a pint of water or sanitizer into each side of the pump head.
3. Confirm the Direction and Speed dials (**3 & 4**) are set to 0 on both remote & control panel. Connect your tubing lines and plug in the pump.
4. Use the bottom left switch (**1**) to choose between controlling the pump using the remote (**B**) or local panel (**A**).
5. Rotate the large red switch (**5**) to a vertical ON position to feed the pump power. You will see the status indicator light (**2**) flash on briefly and turn back off.
6. Now you can use the second black switch (**3**) to control whether the fluid will move forward (**Left**) or reverse (**Right**)
7. Then turn the speed dial (**4**) up from 0, and you will start pumping! The speed control allows you to pump from 0-100% of speed.
8. When done pumping, turn the unit to 0 on the speed control (**4**), then directional control (**3**), and then turn the large red switch (**5**) to a horizontal OFF position. The status indicator light (**2**) will flash briefly on shutdown.
9. For storage, we recommend cleaning the pump head thoroughly and spraying a food grade lubricant in the head to help protect the impeller and keep it from drying out during storage.



A LOCAL PANEL



B WIRED REMOTE