Lallemand Uenolog

LALVIN ICV OPALE 2.0 YSEO

FOR OENOLOGICAL USE

Oenology active dry yeast in the form of round or vermiculated pellets obtained by drying a concentrated yeast culture. Product packaged in laminated foil under vacuum.

10400-06-Y9: 20x500 g pack in a 10 kg carton.

10400-01-Y9: 10 kg carton.

PHYSICAL PROPERTIES

APPEARANCE & ODOUR

- Beige to light brown colour
- Typical yeast smell

INGREDIENT

· Active dry yeast Saccharomyces cerevisiae, E491

PRODUCT SPECIFICATIONS (in compliance with OIV Codex)

Viable yeast Dry matter Coliform	> 10 ¹⁰ CFU/g > 92 % < 10 ² CFU/g
E. coli	Absent in 1 g
S. aureus	Absent in 1 g
Salmonella	Absent in 25 g
Lactic Acid Bacteria	< 10 ⁵ CFU/g
Acetic bacteria	< 10 ⁴ CFU/g
Moulds	< 10 ³ CFU/g
Yeast of different species	< 10 ⁵ CFU/g

HEAVY METALS TYPICAL ANALYSIS

Lead	< 2 mg / kg
Mercury	< 1 mg / kg
Arsenic	< 3 mg / kg
Cadmium	< 1 mg / kg

PREPARATION

- 1. Rehydrate yeast in 10 times its weight of clean water (temperature between 35° and 40°C).
- 2. Stir gently to dissolve and wait for 20 minutes.
- 3. Add to the must. The temperature difference between the must to be inoculated and the rehydration medium should never be greater than 10°C (if any doubt, please contact your supplier or Lallemand).
- 4. The total duration of rehydration should not exceed 45 minutes.
- 5. Always rehydrate the yeast in a clean container.
- 6. Rehydration in the must is not advisable.

DOSAGE

White wine : 25 - 40 g/hL Red wine : 30 - 50 g/hL

STORAGE and SHELFLIFE

Store in a dry and cool place.

4 years in original sealed packaging. Do not use active dry yeast if the packaging has lost its vacuum.



Product of DANSTAR FERMENT AG

Vejlevej 10 Fredericia DK-7000 Denmark Subsidiary of Lallemand Inc. The information herein is based on current available data and is believed to be correct. No warranty, express or implied, is made regarding data accuracy, merchantability or hazards associated with product use. The user is responsible for determining product suitability, conditions of use and all associated hazards.

LALVIN ICV OPALE 2.0 (YSEO) - 28 SEPTEMBER 2015